

for a **Connected** World

850 MHz Whisper Antenna

Outdoor - ID0850 Indoor - ID850



850 MHz DIRECTIONAL IN-BUILDING WHISPER ANTENNA

The widespread use of cellular phones and wireless network applications inside buildings has increased the need for antenna systems that can provide considerable gain over traditional dipole antennas.

Laird Technologies' in-building wireless antennas are particularly applicable in environments where aesthetics and wide angle coverage are necessary for successful wireless deployment. Their surprisingly small size allow the antennas to be hidden almost anywhere, providing an invisible solution for most applications.

SPECIFICATIONS		
Element type	Air-loaded patch	
Frequency range	806 – 896 MHz	
Peak gain	7.5 dBi	
Polarization	Linear	
Azimuth 3dB beamwidth	80°	
Elevation 3dB beamwidth	60°	
Impedance	50 ohms	
Maximum input power	50 watts	
VSWR (min. performance)	2.0:1	
Housing (indoor)	ABS	
Housing (outdoor)	Kydex - UV tolerance rated to 7 years	
Dimensions (L x W x H)	28.4 x 22.4 x 5.6 cm	
Operating/storage temperature	-40° to +70°C	

MODEL #	REFERENCE #	CONNECTOR	HOUSING
ID850-SF00	CAF95978	SMA-female panel	ABS
IDO850-NF00	CAF94122	N-female panel	Kydex

MOUNTING OPTIONS

- Wall-mount bracket & screws included
- Indoor optional brackets: 2" indoor pan/tilt mount (IMI-02C) and 5" indoor pan/tilt mount (IMI-05C)
- Outdoor optional brackets: 5" outdoor metal pan/tilt mount (IMO-05B) and 8" outdoor metal pan/tilt, wall/pole mount (IMP-08A)





global solutions: local support ™

Americas: +1.847 839.6907 IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12 IAS-EUSales@lairdtech.com Asia: +1.65.6.243.8022 IAS-AsiaSales@lairdtech.com

ANT-DS-ID850 0909

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable, Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies from the Laird Technologies that the Laird Technologies that the Laird Technologies Logy, and other marks are used pursuant to the Laird Technologies Logy, and other marks are used marks or registered trade marks of Laird Technologies. Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.