

# **SL17182P Dual-Port Omni Antenna**



## 1850-1990 MHz AND 1710-1755/2110-2155 MHz **CEILING MOUNT, PANEL ANTENNA**

The Laird SL17182P is a dual-port, dual-band, linearly polarized 2 dBi omni-directional panel antenna. The optimized design provides pattern coverage for PCS band requirements combined with the 1710-1755 MHz portion of the DCS band and the 2110-2155 MHz band. The specifically shaped pattern provides top performance from a ceiling mount location. The antenna is also uniform and symmetrical, allowing systems integrators the ability to precisely determine cell size—a major benefit in determining cell overlap and density for in-building systems.

With a small footprint and slim silhouette, the antenna is ideal for any office or retail space where a premium is placed on complementary, unobtrusive aesthetics. Standard with two integrated plenum-rated coax pigtails and SMA male connectors, the SL17182P also accomodates implementation of alternative coax and connector configurations.


#### FEATURES **V**ROHS


- Multi-band coverage from 1 710-2155 MHz
- Dual-port design does not require diplexers
- Neutral color and low silhouette

PARAMETER	SPECIFICATION
Frequency Range (MHz)	1710-1755, 1850-1990 2110-2155
Gain (dBi)	2 (nominal)
E-Plane Beamwidth	65°
H-Plane Beamwidth	Omni-directional
Polarization	Linear
Weight (Ant. Only) lb. (kg)	0.63 (28)
VSWR	2.0:1
Mount Style	Ceiling mount
Dimensions (in)	6" x 6" x 1.25"
Pigtail	36"
Enclosure	ABS
Power (Watts)	2
RF Connectors	SMA (m)

### **MARKETS**

- Corporate offices
- Shopping malls
- Transportation centers





2.15 GHz Port 2

Americas: +1.847 839.6925 IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941 IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127 IAS-AsiaSales@lairdtech.com

www.lairdtech.com

#### ANT-DS-SL17182P 1115

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be laible for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registreed trademarks of Laird Laird. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.