



DESCRIPTION

The **PDB-C152SM** is a blue enhanced PIN silicon photodiode in a photoconductive mode packaged in a water clear surface mount package.

FEATURES

- Surface Mount
- Photoconductive
- High Speed
- Low cost

RELIABILITY

Contact Luna for recommendations on specific test conditions and procedures.

APPLICATIONS

- Industrial Controls
- Opto Switches
- Opto Counters



ABSOLUTE MAXIMUM RATINGS

SYMBOL	MIN	MAX	UNITS	
Reverse Voltage	-	- 50	V	$T_a = 23^{\circ}\text{C}$ UNLESS OTHERWISE NOTED
Storage Temperature	-40	- +125	$^{\circ}\text{C}$	-
Operating Temperature	-40	to +80	$^{\circ}\text{C}$	-
Soldering Temperature*	-	- +240	$^{\circ}\text{C}$	-

* 1/16 inch from case for 3 seconds max.

OPTO-ELECTRICAL PARAMETERS

T_a = 23°C UNLESS NOTED OTHERWISE

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Short Circuit Current	H= 100 fc, 2850 K	8	10	-	μA
Dark Current	V _R = 10 V	-	2	10	nA
Shunt Resistance	V _R = 10 mV	500	-	-	GΩ
Junction Capacitance	V _R =10V; f = 1 MHz	-	15	20	pF
Spectral Application Range	Spot Scan	400	-	1100	nm
Breakdown Voltage	I=10 μA	50	100	-	V
Noise Equivalent Power	V _R =10V@λ= Peak	-	1.5x10 ⁻¹³	-	W/√Hz
Response Time**	RL = 1KΩ, V _R = 50 V	-	50	-	nS

**Response time of 10% to 90% is specified at 660nm wavelength light.

TYPICAL PERFORMANCE

SPECTRAL RESPONSE

