BUSSMANN SERIES

HTC

PCB Fuse accessories for 5 mm fuses




PCB Fuse Blocks

HTC-15M

- 250 V, 6.3 A, 1.6 W
- · Tin plated brass terminals
- cURus: Guide IZLT2 & IZLT8, File # 14853
- · Cover available:
 - HTC-150M (Transparent)
 - HTC-140M (Beige/Natural)






HTC-60M

- 250 V, 6.3 A, 1.6 W
- · Tin plated bronze terminals






PCB Fuse Clips

HTC-200M

- · Tin plated bronze
- Tape and fan fold packed


* # #



HTC-210M

· Tin plated brass







Mounting Holes

.394"

.002" Dia. (Typ.)

- 1.303" (33.1mm

.461" Printed Circuit (11.7mm) Board

PCB Fuse Holders

HTC-45M

• 250 V, 10 A, 2.5 W

· Bayonet cap/carrier


Operating temperature range: -30 °C to + 85 °C

• cURus: Guide IZLT2 & IZLT8 File + 1853

Not recommended for new 1.0511±.002 1.00±.0511±.002 1.00±.0511±.002 1.00±.0511±.002 1.00±.0511±.002 1.00±.0511±.002

HTC-50M

- 250 V, 10 A, 2.5 W
- Bayonet cap/carrier
- Operating temperature range: -30 °C to + 85 °C
- cURus: Guide IZLT2 & IZLT8 File # 14853



Common HTC specifications

- Solerability: In accordance with IEC 68-2-20
- Molded materials: UL94 V-0 (HTC-15M UL94 V-1)

Packaging Codes	
Packaging code prefix	Description
Blank	10 pieces packed into a carton (Not available on HTC-210M)
BK-	100 pieces packed into a cardboard shelf package
BK1-	1000 pieces packed into a poly bag
AP-	1000 pieces per box in Ammo pack (HTC-200M only)

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton Electronics Division 1000 Eaton Boulevard Cleveland, OH 44122 United States www.eaton.com/electronics

© 2017 Eaton All Rights Reserved Printed in USA Publication No. 2110 BU-MC17076 December 2017

