

Timers

Delay on Operate

Type DAA01, PAA01

CARLO GAVAZZI



DAA01



PAA01

- Time range 0.1 s to 100 h
- Knob selection of time range
- Knob adjustable time setting
- Automatic start
- Repeatability: $\leq 0.2\%$
- Output: 8 A SPDT or 2 x 8 A SPDT relays
- For mounting on DIN-rail in accordance with DIN/EN 50 022 or Plug-in
- 22.5 Euronorm or 36 mm plug-in module housing
- Combined AC and DC power supply
- LED indication for relay status and power supply ON

Product Description

Multi-voltage delay on operate timer with 7 selectable time ranges within 0.1 s and

100 h. For mounting on DIN-rail (DAA01) or plug-in (PAA01).

Ordering Key

DAA 01 C M24

Housing _____
 Function _____
 Type _____
 Item number _____
 Output _____
 Power supply _____

Type Selection

Mounting	Output	Housing	Supply: 24 VDC and 24 to 240 VAC	Supply: 24 to 240 VAC/DC
DIN-rail	1 x SPDT 2 x SPDT	D-Housing	DAA01CM24	DAA01DM24
Plug-in	1 x SPDT 2 x SPDT	P-Housing	PAA01CM24	PAA01DM24

Time Specifications

Time ranges Knob selectable	0.1 to 1 s 1 to 10 s 6 to 60 s 60 to 600 s 0.1 to 1 h 1 to 10 h 10 to 100 h
Setting accuracy	$\leq 5\%$
Repeatability	$\leq 0.2\%$
Time variation Within rated power supply Within ambient temperature	$\leq 0.05\%/V$ $\leq 0.2\%/^{\circ}C$
Reset Power supply interruption	≥ 200 ms

Output Specifications

Output	1 or 2 x SPDT relays
Rated insulation voltage	250 VAC (rms)
Contact Ratings (AgSnO ₂)	μ
Resistive loads	AC 1 8 A @ 250 VAC DC 12 5 A @ 24 VDC
Small inductive loads	AC 15 2.5 A @ 250 VAC DC 13 2.5 A @ 24 VDC
Mechanical life	$\geq 30 \times 10^6$ operations
Electrical life	$\geq 10^5$ operations (at 8 A, 250 V, $\cos \varphi = 1$)
Operating frequency	< 7200 operations/h
Dielectric strength	
Dielectric voltage	2 kVAC (rms)
Rated impulse withstand voltage	4 kV (1.2/50 μ s)

Supply Specifications


Power supply Rated operational voltage through terminals: (DAA01C) A1, A2 or 2, 10 (PAA01C) (DAA01D) A1, A2 or 2, 10 (PAA01D)	Overvoltage cat. III (IEC 60664, IEC 60038) 24 VDC $\pm 15\%$ and 24 to 240 VAC + 10% -15%, 45 to 65 Hz 24 to 240 VAC/DC + 10% - 15%, 45 to 65 Hz	Voltage interruption	≤ 10 ms
		Rated operational power AC supply DC supply	4 VA 1.5 W




General Specifications

Power ON delay		≤ 100 ms
Reaction time Instantaneous contact		< 20 ms from power ON
Indication for Power supply ON Output relays ON		LED, green LED, yellow (flashing when timing)
Environment		(EN 60529) IP 20 Pollution degree 3 (DAA01), 2 (PAA01) (IEC 60664)
Operating temperature Storage temperature		-20° to +60°C, R.H. < 95% -30° to +80°C, R.H. < 95%
Housing	Dimensions	DAA01 22.5 x 80 x 99.5 mm PAA01 36 x 80 x 94 mm
	Weight	Approx. 130 g
Screw terminals (DAA01) Tightening torque		Max. 0.5 Nm according to IEC EN 60947
Approvals		UL, CSA RINA (DAA01 only)
CE marking		Yes
EMC		Electromagnetic Compatibility According to EN 61000-6-2 According to EN 61000-6-3
Timer Specifications		According to EN 61812-1

Operating Diagram



Wiring Diagrams



Mode of Operation

The yellow LED, flashing when timing, is ON as soon as the relay turns ON.

The second relay can operate as instantaneous or delayed changeover contact. The selection is made by a DIP-switch placed under the plastic door on the device's front.

The set delay period begins as soon as the power supply is connected. At the end of the set delay the relay operates and does not release until the power supply is interrupted for at least 200 ms. If the power supply is interrupted for at least 200 ms before the relay operates the time is set to zero and the circuit is ready for a new time period.

Time Setting

Centre knob:
Time setting on relative scale: 1 to 10 with respect to the chosen range

Lower knob:
Setting of time range

Dimensions

